

PRODUCT COPY: AIRWORX 55T FACELIFT

AIRWORX-55T

BIGGER RESULTS FROM A SMALLER MACHINE! A FRESH LOOK FOR THE AIRWORX 55T

Compacting its size hasn't meant shortchanging its performance.

With a range of new features, the AIRWORX 55T upgrades productivity and efficiency.

WHAT'S NEW?

- Load Easier and transport upright with the new shorter filter silo.
- Dial up suction capacity with 15% additional primary filter surface area.
- Operate easily with improved ergonomics
- Increase project productivity and efficiency
- Improve manueverability where it's tight

KEY UPDATED FEATURES: (see diagram on next page)

- 260mm lower in height... makes van/trailer transport easy
- New filter sock set up 19 socks that really suck
- 100mm shorter frame no more oversized pallet loads and improved performance in tight spaces
- Repositioned accessory machine outlet easier access
- Updated labelled control panel
- Broom and wand transport handles
- Easy access bag changing





260mm lower in height

Broom and wand transport handles

100mm shorter frame no more oversized pallet loads & improved performance in tight spaces

Updated labelled control panel





Easy van/trailer storage and transportation!



Repositioned accessory machine outlet for easier access





Applications:

- Elimination of hazardous airborne dust in the grinding/sanding o concrete/masonry/timber applications.
- Industrial applications where high suction is required.

Features:

- Frequency controlled vacuum pump offering the following benefits:
 - i. 40% more airfl ow than standard machines on regular power supply.
 - **ii.** Variable suction control (can be used for hand grinders through to large fl oor grinding machines).
 - iii. Generator friendly soft start.
 - iv. Sophisticated electronic motor protection.
 - v. Automatic direction correction.
- Time saving radio controlled on/off (but also includes manual on/off).
- Reliable 2-stage filter sock & micro filter particle filtration.
- Large puncture proof wheels for easy transportation over rougher surfaces.
- Excellent ground clearance.
- Fits through standard doors.
- Rear "bull horns" for transportation of power
- leads & vacuum hoses.
- Easily folds forward to enable compact transportation.
- Unique bag-disposal system for containment of messy and hazardous substances (continuous bag compatable).
- Washable polyester filters (M-Class only).
- Power outlet for grinding machine.
- Highly mobile & fl exible unit.
- All metal super-industrial strength construction.
- 3" (75mm) hose inlet.
- Quiet operation with integrated WORX+ silencer.
- H class option 99.999% @ 1μm particle size.





TECHNICAL INFORMATION:

Motor (3~Phase)	5.5kW 380-480V
Rated Current	15A Max (6-12A normal use depending on speed setting)
Weight	260 kg
Max Airflow (Approximately)	650 m3 / hr
Maximum Vacuum	300 mbar
Suction inlet	Ø75 mm
Primary filtration surface area	2.78m2
Micro filter surface area	6.5 m2
Length x Width x Height (Upright)	1200 x 760 x 1700mm
Length x Width x Height (Folded)	1870 x 760 x 1325mm

