

# **SAFETY DATA SHEET**

## **REDI-FIX**

Infosafe No.: LQBHJ ISSUED Date : 23/11/2022 ISSUED by: WORX PLUS UNIT TRUST

## Section 1 - Identification

Product Identifier REDI-FIX

Company Name WORX PLUS UNIT TRUST (ABN 19 445 818 014)

Address 56 Jersey Road, Bayswater VIC 3153 Australia

Telephone/Fax Number Tel: 1300 897 873

**Emergency Phone Number** 131 126

Recommended use of the chemical and restrictions on use

Chemical anchoring application & concrete patching / repair

#### **Other Information**

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Worx Plus Unit Trust, makes no representations as to the completeness or accuracy thereof. Information is supplied on the conditions that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Worx Plus Unit Trust or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

## Section 2 - Hazard(s) Identification

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye damage/irritation: Category 2A Sensitisation - skin: Category 1

Signal Word (s) WARNING

Hazard Statement (s) H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Pictogram (s)



#### **Precautionary Statement – Prevention**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### **Precautionary Statement – Response**

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

#### **Precautionary Statement – Disposal**

P501 Dispose of contents/container to an approved waste disposal plant.

## Section 3 - Composition and Information on Ingredients

#### Ingredients

Name	CAS	Proportion
Ethylstyrene	28106-30-1	1-10 %
dibenzoyl peroxide	94-36-0	1-3 %
N,N-dimethyl-p-toluidine	99-97-8	<1 %
Ingredients determined not to be hazardous		Balance

### Section 4 - First Aid Measures

#### Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

#### Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

#### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

#### Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

#### **First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

#### Advice to Doctor

Treat symptomatically.

#### Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

## **Section 5 - Firefighting Measures**

#### Suitable Extinguishing Media

Foam, dry chemical powder or carbon dioxide.

#### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and other pyrolysis products typical of burning organic material.

#### Specific hazards arising from the chemical

This product will burn if exposed to fire. Heating can cause expansion or decomposition leading to violent rupture of containers.

Decomposition Temperature

Not available

#### Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

## **Section 6 - Accidental Release Measures**

#### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

### Section 7 - Handling and Storage

#### Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

#### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents, acids, acid chlorides, acid anhydrides and chloroformates. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

### **Section 8 - Exposure Controls and Personal Protection**

#### **Occupational exposure limit values**

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Dibenzoyl peroxide TWA: 5 mg/m<sup>3</sup> Note: Sen

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week. 'Sen' Notice: The substance may cause sensitization by skin contact or by inhalation. Source: Safe Work Australia

**Biological Monitoring** No biological limits allocated.

**Control Banding** Not available

#### **Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

#### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/dust filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

#### Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

#### Hand Protection

Wear gloves of impervious material such as PVC. Final choice of appropriate gloves will vary according to individual circumstances. i. e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

#### **Thermal Hazards**

No further relevant information available.

#### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Properties	Description	Properties	Description
Form	Paste	Appearance	Non slump paste
Colour	Various colours	Odour	Characteristic
Melting/Freezing Point	Not available	Boiling Point	Not available
Decomposition Temperature	Not available	Solubility in Water	Insoluble
Specific Gravity	Not available	рН	Not available
Vapour Pressure	Not available	Relative Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Volatile Component	VOC: 0.66 g/L	Pour Point	Not available
Partition Coefficient: n- octanol/water (log value)	Not available	Density	Not available
Flash Point	Not available	Flammability	Combustible
Auto-Ignition Temperature	Not available	Explosion Limit - Upper	Not available
Explosion Limit - Lower	Not available	Relative Density	1.61
Particle Characteristics	Not available		

## **Section 9 - Physical and Chemical Properties**

Page 4 / 9

## Section 10 - Stability and Reactivity

#### Reactivity

Reacts with incompatible materials.

Chemical Stability Stable under normal conditions of storage and handling.

#### Possibility of hazardous reactions

Reacts with incompatible materials.

### **Conditions to Avoid**

Heat, open flames and other sources of ignition.

## Incompatible Materials

Avoid oxidising agents, acids, acid chlorides, acid anhydrides and chloroformates.

#### **Hazardous Decomposition Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and other pyrolysis products typical of burning organic material.

### **Hazardous Polymerization**

Will not occur.

## **Section 11 - Toxicological Information**

#### **Toxicology Information**

No toxicity data available for this material. The available acute toxicity data for the ingredient/s is/are given below.

Acute Toxicity - Oral dibenzoyl peroxide LD50(rat): > 950 mg/kg

N,N-dimethyl-p-toluidine LD50(rat): 1650 mg/kg

#### Acute Toxicity - Inhalation

N,N-dimethyl-p-toluidine LC50(rat): > 1.4 mg/l/4H

#### Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

#### Inhalation

Inhalation of dusts/vapors may irritate the respiratory system.

### Skin

May be irritating to skin. The symptoms may include redness, itching and swelling. May cause an allergic skin reaction. Open cuts, abraded or irritated skin should not be exposed to this material

#### Skin Corrosion/Irritation

Dibenzoyl peroxide Skin effects (MAK): very weak

#### Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

#### Serious Eye Damage/Irritation

Dibenzoyl peroxide Eye (rabbit): 500 mg/24h - mild

## **Respiratory Sensitisation**

Not expected to be a respiratory sensitiser.

#### **Skin Sensitisation**

May cause an allergic skin reaction.

#### **Germ Cell Mutagenicity**

Not considered to be a mutagenic hazard.

#### Carcinogenicity

Not considered to be a carcinogenic hazard.

N,N-dimethyl-p-toluidine is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Dibenzoyl peroxide is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

#### **Reproductive Toxicity**

Not considered to be toxic to reproduction.

#### **STOT - Single Exposure**

Not expected to cause toxicity to a specific target organ.

#### **STOT - Repeated Exposure**

Not expected to cause toxicity to a specific target organ.

#### Aspiration Hazard

Not expected to be an aspiration hazard.

#### **Chronic Effects**

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Most arylamines are very toxic to the blood cell-forming system, and they produce methaemoglobinaemia in humans. High doses congest the spleen and then cause formation of sarcomas (a type of malignant tumour).

### Section 12 - Ecological Information

#### Ecotoxicity

No ecological data available for this material. The available ecological data for the ingredients is given below:

#### Persistence and degradability

Dibenzoyl peroxide Persistence in Water/Soil: LOW (Half-life = 14 days) Persistence in Air: LOW (Half-life = 21.25 days)

N,N-dimethyl-p-toluidine Persistence in Water/Soil: HIGH Persistence in Air: HIGH

#### Mobility

Dibenzoyl peroxide LOW (KOC = 771)

N,N-dimethyl-p-toluidine LOW (KOC = 124.8)

**Bioaccumulative Potential** Ethylstyrene MEDIUM (BCF = 619)

Dibenzoyl peroxide LOW (LogKOW = 3.46)

N,N-dimethyl-p-toluidine LOW (LogKOW = 2.81)

Other Adverse Effects Not available

**Environmental Protection** Prevent this material entering waterways, drains and sewers. Acute Toxicity - Fish Dibenzoyl peroxide LC50 (fish): 0.0602 mg/L/96hr

N,N-dimethyl-p-toluidine LC50 (fish): 46 mg/L/96hr

## Acute Toxicity - Algae

Dibenzoyl peroxide EC50 (Algae or other aquatic plants): 0.0422 mg/L/72hr

N,N-dimethyl-p-toluidine EC50 (Algae or other aquatic plants): 22mg/L/72hr

Acute Toxicity - Other Organisms Dibenzoyl peroxide EC50 (Crustacea): 0.11 mg/L/48hr

N,N-dimethyl-p-toluidine EC50 (Crustacea): 13.7 mg/L/48hr

Chronic Toxicity - Algae Dibenzoyl peroxide NOEC (Algae or other aquatic plants): 0.02 mg/L/72hr

Hazardous to the Ozone Layer This product is not expected to deplete the ozone layer.

## Section 13 - Disposal Considerations

#### **Disposal Considerations**

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations. To minimise personal exposure, refer to Section 8 - Exposure Controls and Personal Protection.

### Section 14 - Transport Information

#### **Transport Information**

Road and Rail Transport (ADG Code): Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

Marine Transport (IMO/IMDG): Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport (ICAO/IATA): Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

ADG U.N. Number None Allocated

ADG Proper Shipping Name None Allocated

ADG Transport Hazard Class None Allocated

Special Precautions for User Not available

IMDG Marine pollutant No

#### Transport in Bulk Not available

## Section 15 - Regulatory Information

#### **Regulatory Information**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule Not Scheduled

Montreal Protocol Not listed

Stockholm Convention Not listed

Rotterdam Convention Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL) Not available

Agricultural and Veterinary Chemicals Act 1994 Not available

Basel Convention Not available

#### **Section 16 - Any Other Relevant Information**

#### **Date of Preparation**

SDS Created: November 2022

Version Number

1.0

#### **Literature References**

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

#### **Contact Person/Point**

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Worx Plus Unit Trust, makes no representations as to the completeness or accuracy thereof. Information is supplied on the conditions that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Worx Plus Unit Trust or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

## **END OF SDS**

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.